

# Linx 7900



## Are you paying more than you should on additional features for your current coding equipment?

The Linx 7900 range of printers offer advanced additional features as standard, providing value for money with no hidden costs.

### Simple printer control

- Linx Insight® enables remote monitoring from a smart phone, plus message download and control from a PC
- QuickSwitch® software allows simple and accurate code changes using a barcode scanner
- USB port means easy transfer of messages between printers.

### Lowest running costs

- Intelligent ink system enables up to 9000 hours\* between scheduled service intervals
- 18 month warranty\* on printer from installation at no extra cost
- Mistake-free message editing is provided by customisable on-screen prompts, to reduce coding errors.

### Increased production uptime

- FullFlush® system automatically cleans and dries the printhead and conduit at every shutdown
- SureFill® enables fast, mistake-free refills, everytime.

### Additional standard features

- Ethernet port for easy connectivity to the web or factory systems
- Prints up to 3 lines of text, logos, barcodes and 2D Data Matrix codes, with 5 line upgrade available

- RS232 connectivity for line integration
- Connectivity for two product detectors and shaft encoder, for easy installation with conveyors and other equipment
- Low fluid consumption with a range of versatile inks, to reduce running costs and emissions.

### Linx Insight

The new Linx Insight offers end users the opportunity to control their printers remotely. The key benefits include:

- Status view of current message, warnings and service life from a smart phone or PC, for increased control of your production line
- Remote message download or upload from a PC, which helps to prevent coding errors.

\*Excludes Spectrum/FG variants



THINKING ALONG YOUR LINES

# Linx 7900

### Dimensions (mm)

Top Elevation




Front Elevation




Side Elevation



Printhead



Midi SRRA Printhead



### Print speeds and printhead options

Printhead	Micro	Mini	Ultima*	Midi*	Midi EC	Ultima plus	Midi plus
Lines of print supported	1,2,3 or 4	1 or 2	1,2 or 3	1,2,3,4 or 5	1,2 or 3	1,2 or 3	1,2,3,4 or 5
Character height range	1.1 to 8.0 mm	1.4 to 6.7 mm	1.8 to 7.8 mm	1.8 to 12 mm	1.8 to 10.5 mm	2.1 to 9.5 mm	2.1 to 13.8 mm
Maximum speed: single line print, wide pitch, High Performance print option	8.41 m/s	6.83 m/s	6.25 m/s	6.28 m/s	6.28 m/s	7.28 m/s	2.10 m/s
Maximum number of characters per second	2222	2667	2222	1905	1905	2133	821
High Performance (HP) print option	○	○	○	○	○	○	○
Linx 7900	○	○	●	○	○	○	○
Linx 7900 Spectrum (for pigmented inks)						●	○
Linx 7900 Solver (for lowest solvent consumption)	○		●	○			
Linx 7900 Swift (for high speed lines)		●					
Linx 7900FG (for Food Grade inks)					●		
Linx 7900BC (for wet bottle coding)			●	○			

\*For certain inks, Ultima A and Midi A printheads replace Ultima and Midi printheads, to provide reliable performance. Print speeds are unchanged.

### General features

- Single button startup and shutdown
- Simple menu-driven WYSIWYG message creation and editing
- SureFill® mistake-proof refill system and on-screen fluid level indicators
- Integral QWERTY keyboard (full size) and ¼ VGA back-lit colour display, printer status indicators (4 LEDs)
- USB port for copy and back up of message and printer settings
- FullFlush® automatic printhead and conduit flush
- Saving remote field data over a power cycle
- Linx Insight® remote printer control and status view
- Auto power-off
- Automatic diagnostics
- Multiple operator languages (user selectable)
- Dynamically adjusted service interval up to 9000 hours (not available with Spectrum, FG)
- Password-protected functions
- Dynamic message and logo storage capacity
- Prompted fields

### Programming and printing facilities

- Fixed and variable text
- Upper and lower case characters
- Graphics/logo printing
- Logo creation and editing, on-screen
- QuickSwitch® message selection and editing using bar code scanner
- Bar codes EAN 8, EAN 13, 2 of 5, ITF, Code 39, Code 128, UPC-A, GS1 128 linear barcode
- Data Matrix 2D codes
- Bold factor (up to 10 times)
- Height, width and delay functions for easy code sizing and positioning
- Standard and user-definable formats for shift coding
- 7900FG: Egg coder configuration matches service interval to flock life, and provides reliable operation in barn environments
- 7900 Spectrum: Inverse Image barcodes and text e.g. white on black
- Remote communications interface
- Real-time clock functions
- Automatic date forward function
- Batch coding and counting
- Sequential numbering and messages
- Dynamic reverse and invert printing for traversing lines
- Rotated character ('tower') printing
- Message creation/editing whilst printing
- Timed-message function
- Flexible print trigger options
- LogoJet PC-based message and logo creation software
- 7900 Swift: narrow fonts for coding onto small print areas
- 7900 Spectrum: programmable pre-set ink mix times

### Printhead options

- 2m conduit
- 4m conduit (not available with Solver or FG printers)
- 90° printhead configuration
- Positive air purge to printhead
- Cutaway printhead cover tube
- Magnetic shielded cover tube
- Midi Short Reach Right Angled (SRRA) printhead (for 7900, Solver), length 130mm

### Ink range

	Linx 7900	Linx 7900 Spectrum	Linx 7900 Solver	Linx 7900 Swift	Linx 7900BC	Linx 7900FG
Linx MEK base (dye-based/soft pigmented)	●	● (soft pigmented)	●	● (1240, 1405)	● (1058)	
Linx mixed base	●		●			
Linx ethanol base	●					
Linx MEK base High Opacity pigmented inks		●				
Linx Food Grade inks						●

### Connections/interfacing for

- Shaft encoder
- Primary and secondary product detectors
- External single stage alarm output
- USB
- RS232
- Ethernet
- External multi-stage alarm output
- Parallel I/O
- Multiple printer triggering from single product detector/shaft encoder
- Volt-free contact alarm connection (e.g. for use with external mains-driven alarm)

### Physical characteristics

Base and enclosure	Stainless steel
IP55 environmental protection rating**	● (not available with 7900 Spectrum)
IP65 environmental protection rating**	○ (standard for 7900 Spectrum, not available with 7900FG printers)
Mounting options	Bench or console
Operating temperature range	5 – 45°C (FG: 0 – 40°C)
Humidity range (r.h., non-condensing)	90% max
Power supply	100-230V, 50/60Hz
Power consumption	60W (typical when printing, excluding FG and Spectrum)
Power rating	200W
Weight	21kg (Spectrum and FG, 24kg)

### Regulatory approvals

- GS
  - CE
  - GOST R
  - NRTL
  - FCC
- Key ● standard ○ option \*\*Independently verified – certificates available on request

www.linxglobal.com



THINKING ALONG YOUR LINES



For more information, contact Linx Printing Technologies Ltd, Burrel Road, St Ives, Cambridgeshire PE27 3LA, UK. Telephone +44 (0)1480 302100 Fax +44 (0)1480 302116 email sales@linxglobal.com www.linxglobal.com

Linx, SureFill, QuickSwitch, FullFlush, Linx Insight and Logojet are registered trademarks of Linx Printing Technologies Ltd. © Linx Printing Technologies Ltd 2012.